

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021**Neoval MTO 300 Aerosol**

Material number 820-10C

Page: 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name: Neoval MTO 300 Aerosol

UFI: E020-00VJ-Y00A-29WR

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Lubricating oil with excellent anti-corrosion effect.

1.3 Details of the supplier of the safety data sheet

Company name: EUROTECH Maier Ernst GmbH

Street/POB-No.: Herrschaftswiesen 5

Postal Code, city: AT-6842 Koblach

WWW: www.eurotech.at

E-mail: office@eurotech.at

Telephone: +43 (0)5523 53852

Telefax: +43 (0)5523 53852 4

Department responsible for information:

Telephone: +43 (0)5523 53852, Email: office@eurotech.at

Additional information: This safety data sheet pertains to the following products:

820100 Neoval MTO 300 Aerosol 100 ml

820312 Neoval MTO 300 Aerosol 400 ml in a carton of 12

820324 Neoval MTO 300 Aerosol 400 ml in a carton of 24

1.4 Emergency telephone number

Giftzentrale Wien, Telephone: +43 (0)1-4064343

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to EC regulation 1272/2008 (CLP)**

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

2.2 Label elements**Labelling (CLP)**

Signal word:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021

Neoval MTO 300 Aerosol

Material number 820-10C

Page: 2 of 11

Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

Exposure to temperatures exceeding 50 °C will increase pressure: resulting in danger of bursting or explosion.

Potentially explosive mixtures may form if adequate ventilation is not provided.

Inhaling can lead to irritations of the respiratory tract and mucous membrane.

Higher doses may lead to a narcotic effect.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Paraffin oil (CAS 8042-47-5), Corrosion inhibitors, Additives, Propellant.

Hazardous ingredients:

Ingredient	Designation	Content	Classification
EC No. 232-455-8 CAS 8042-47-5	White mineral oil (petroleum)	< 42 %	Asp. Tox. 1; H304.
EC No. 260-991-2 CAS 57855-77-3	Calcium bis (dinonylnaphthalenesulphonate)	1 - 2 %	Skin Irrit. 2; H315. Eye Irrit. 2; H319.
EC No. 203-448-7 CAS 106-97-8	n-Butane, pure	20 - 30 %	Flam. Gas 1; H220. Press. Gas (Liq.); H280.
EC No. 200-827-9 CAS 74-98-6	Propane	20 - 30 %	Flam. Gas 1; H220. Press. Gas (Comp.); H280.

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection!

In case of inhalation: Provide fresh air. Seek medical treatment in case of troubles.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021

Version: 20.0

Language: en-GB

Date of print: 15/7/2021

Neoval MTO 300 Aerosol

Material number 820-10C

Page: 3 of 11

- Following skin contact: Remove residues with soap and water. Do not use solvents or thinners. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.
- After swallowing: Do not induce vomiting. Rinse mouth and seek medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media:

Foam, carbon dioxide

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated.
Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited.
May form dangerous gases and vapours in case of fire.
Furthermore, there may develop: Sulphur oxides, carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Hazchem-Code: -

Heating will lead to pressure increase: Danger of bursting and explosion.
Cool endangered containers with water spray and, if possible, remove from danger zone.
Move undamaged containers from immediate hazard area if it can be done safely.
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Do not allow fire water to penetrate into surface or ground water.
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe spray. Avoid contact with the substance.
Eliminate all ignition sources if safe to do so. Provide adequate ventilation.
Wear appropriate protective equipment. Keep unprotected people away.
Cordon off downwind area at risk and warn inhabitants.
Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains.
If necessary notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out). Never return spills in original containers for re-use.

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.
When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Use only non-sparking tools. Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store containers in upright position.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.
Do not store together with combustible or self-igniting materials or any highly flammable solids.

7.3 Specific end use(s)

No information available.



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
106-97-8	n-Butane, pure	Great Britain: WEL-STEL	1810 mg/m ³ ; 750 ppm
		Great Britain: WEL-TWA	1450 mg/m ³ ; 600 ppm

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

Personal protection equipment

Occupational exposure controls

- Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use filter type A (= against vapours of organic substances) according to EN 14387.
- Hand protection: Protective gloves according to EN 374.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed goggles according to EN 166.
- Body protection: Flame retardant, antistatic and chemical resistant protective clothing.
- General protection and hygiene measures:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Do not breathe spray. Do not get in eyes, on skin, or on clothing.
Contaminated work clothing should not be allowed out of the workplace.
When using do not eat or drink. Take off contaminated clothing and wash it before reuse.
Wash hands thoroughly after handling.
When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance: Physical state at 20 °C and 101.3 kPa: liquid
Form: Aerosol
Colour: yellowish
- Odour: characteristic
- Odour threshold: No data available
- pH: No data available
- Melting point/freezing point: -33 °C (DIN 51376)
- Initial boiling point and boiling range: -44 °C
- Flash point/flash point range: -97 °C
- Evaporation rate: No data available
- Flammability: Extremely flammable aerosol.
- Explosion limits: LEL (Lower Explosion Limit): 0.60 Vol-%
UEL (Upper Explosive Limit): 9.50 Vol-%

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021**Neoval MTO 300 Aerosol**

Material number 820-10C

Page: 6 of 11

Vapour pressure:	at 20 °C: 7.7 hPa
Vapour density:	No data available
Density:	at 20 °C: 0.45 g/mL
Water solubility:	at 20 °C: slightly soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not self-igniting
Decomposition temperature:	> 500 °C
Viscosity, kinematic:	No data available
Explosive properties:	Product is not explosive. Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available

9.2 Other information

Ignition temperature: 365 °C

SECTION 10: Stability and reactivity**10.1 Reactivity**

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

None known

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: > 500 °C

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Acute toxicity: LD50 Rat, oral (calculated): > 2000 mg/kg

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021**Neoval MTO 300 Aerosol**

Material number 820-10C

Page: 7 of 11

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Following skin contact: Not an irritant.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

In case of eye contact: Not an irritant.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Based on available data, the classification criteria are not met. Not known to cause sensitization.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.

Symptoms

After eye contact: Mild irritant.

SECTION 12: Ecological information**12.1 Toxicity**

Further details: No data available

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potentialPartition coefficient: n-octanol/water:
No data available**12.4 Mobility in soil**

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021**Neoval MTO 300 Aerosol**

Material number 820-10C

Page: 8 of 11

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste key number: 16 05 04* = Dangerous materials containing gases in pressure containers/Aerosol
* = Evidence for disposal must be provided.

Recommendation: Do not pierce or burn, even after use.
Special waste. Dispose of waste according to applicable legislation.
Do not open with force or incinerate, even when empty.
Do not dispose of with household waste.

Package

Waste key number: 15 01 10* = packaging containing residues of or contaminated by dangerous substances
* = Evidence for disposal must be provided.

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.
Empty carefully and completely, if possible.
Handle empty containers with care. Incineration may cause explosion.

SECTION 14: Transport information**14.1 UN number**

ADR/RID, IMDG, IATA-DGR:
UN 1950

14.2 UN proper shipping name

ADR/RID, IMDG: UN 1950, AEROSOLS
IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID: Class 2, Code: 5F
IMDG: Class 2, Subrisk -, see SP63
IATA-DGR: Class 2.1

**14.4 Packing group**

ADR/RID, IATA-DGR: not applicable
IMDG: -

14.5 Environmental hazards

Marine pollutant: no

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021**Neoval MTO 300 Aerosol**

Material number 820-1OC

Page: 9 of 11

14.6 Special precautions for user**Land transport (ADR/RID)**

Warning board: RID: Kemmler-number 23, UN number UN 1950
Hazard label: 2.1
Special provisions: 190 327 344 625
Limited quantities: 1 L
EQ: E0
Package - Instructions: P207 LP200
Package - Special provisions: PP87 RR6 L2
Special provisions for packing together: MP9
Tunnel restriction code: D

Sea transport (IMDG)

EmS: F-D, S-U
Special provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantities: See SP277
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations - Great Britain**

Hazchem-Code: -
No data available



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021

Neoval MTO 300 Aerosol

Material number 820-1OC

Page: 10 of 11

National regulations - EC member states

Volatile organic compounds (VOC):

< 60 % by weight = 270 g/L

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3, 40, 75 Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances
[Seveso-III-Directive]: P3a

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

- H220 = Extremely flammable gas.
- H222 = Extremely flammable aerosol.
- H229 = Pressurised container: May burst if heated.
- H280 = Contains gas under pressure; may explode if heated.
- H304 = May be fatal if swallowed and enters airways.
- H315 = Causes skin irritation.
- H319 = Causes serious eye irritation.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 31/3/2021
Version: 20.0
Language: en-GB
Date of print: 15/7/2021

Neoval MTO 300 Aerosol

Material number 820-10C

Page: 11 of 11

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL: Occupational Exposure Limit Value
AS/NZS: Australian Standards/New Zealand Standards
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EN: European Standard
EU: European Union
IATA: International Air Transport Association
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
TLV: Threshold Limit Value
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

Reason of change: Changes in section 1: product identifier (UFI)

Date of first version: 5/4/2006

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.