

**Rostex 400ml Aerosoldose**

Material number A400

Page: 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name: Rostex 400ml Aerosoldose

UFI: YS20-K034-Q00S-0D5A

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Rust converter

1.3 Details of the supplier of the safety data sheet

Company name: EUROTECH Maier Ernst GmbH

Street/POB-No.: Herrschaftswiesen 5

Postal Code, city: AT-6842 Koblach

WWW: www.eurotech.at

E-mail: office@eurotech.at

Telephone: +43 (0)5523 53852

Telefax: +43 (0)5523 53852 4

Department responsible for information:

Telephone: +43 (0)5523 53852, Email: office@eurotech.at

1.4 Emergency telephone number

Giftzentrale Wien, Telephone: +43 (0)1-4064343

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to EC regulation 1272/2008 (CLP)**

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2; H315 Causes skin irritation.

Eye Irrit. 2; H319 Causes serious eye irritation.

Skin Sens. 1; H317 May cause an allergic skin reaction.

STOT SE 3; H336 May cause drowsiness or dizziness.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling (CLP)**

Signal word:

Danger

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021

Version: 3.0

Language: en-GB,IE

Date of print: 15/7/2021

Rostex 400ml Aerosoldose

Material number A400

Page: 2 of 14

Hazard statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary statements:	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P261	Avoid breathing vapours/spray.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P405	Store locked up.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700).

2.3 Other hazards

Heating will lead to pressure increase: Danger of bursting and explosion.
Potentially explosive mixtures may form if adequate ventilation is not provided.
Higher doses may have a narcotic effect.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions



Hazardous ingredients:

Ingredient	Designation	Content	Classification
REACH 01-2119475108-36-xxxx EC No. 203-905-0 CAS 111-76-2	2-Butoxyethanol	1 - 10 %	Acute Tox. 4; H302. Acute Tox. 4; H312. Acute Tox. 4; H332. Skin Irrit. 2; H315. Eye Irrit. 2; H319.
REACH 01-2119485493-29-xxxx EC No. 204-658-1 CAS 123-86-4	n-Butyl acetate	1 - 10 %	Flam. Liq. 3; H226. STOT SE 3; H336. (EUH066).
REACH 01-2119457558-25-xxxx EC No. 200-661-7 CAS 67-63-0	Isopropyl alcohol	1 - 10 %	Flam. Liq. 2; H225. Eye Irrit. 2; H319. STOT SE 3; H336.
EC No. 500-033-5 CAS 25068-38-6	Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <=700)	2.5 - 5 %	Skin Irrit. 2; H315. Eye Irrit. 2; H319. Skin Sens. 1; H317. Aquatic Chronic 2; H411.
REACH 01-2119484630-38-xxxx EC No. 200-751-6 CAS 71-36-3	Butan-1-ol	1 - 3 %	Flam. Liq. 3; H226. Acute Tox. 4; H302. Skin Irrit. 2; H315. Eye Dam. 1; H318. STOT SE 3; H335, H336.
REACH 01-2119455851-35-xxxx list no. 918-668-5 CAS 64742-95-6	Hydrocarbons, C9, aromatics	1 - 2.5 %	Flam. Liq. 3; H226. Acute Tox. 4; H332. STOT SE 3; H335, H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411. (EUH066).
REACH 01-2119472128-37-xxxx EC No. 204-065-8 CAS 115-10-6	Dimethyl ether	30 - 50 %	Flam. Gas 1; H220. Press. Gas (Liq.); H280.

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. If the casualty has difficulty breathing, call a doctor immediately.
Following skin contact:	After contact with skin, wash immediately with soap and plenty of water. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Do not induce vomiting. Rinse mouth and seek medical attention immediately.



4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, water spray jet, carbon dioxide.
In case of large fires: water spray jet or alcohol resistant foam.

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air. Beware of reignition.

In case of fire may be liberated: Carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Hazchem-Code: -

Cool endangered containers with water spray and, if possible, remove from danger zone. Heating will lead to pressure increase: Danger of bursting and explosion. Use water spray jet to knock down vapours. Do not allow fire water to penetrate into surface or ground water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so.
Avoid contact with skin and eyes. Do not breathe vapour/aerosol.
In enclosed areas: Provide fresh air.
If higher concentrations occur: Wear self-contained breathing apparatus.
Wear appropriate protective equipment. Keep unprotected people away.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.
If necessary notify appropriate authorities.

**Rostex 400ml Aerosoldose**

Material number A400

Page: 5 of 14

6.3 Methods and material for containment and cleaning up

If possible bring to the outside to enable outgassing.

Collect spillage. Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out). Seal off. Contact expert.

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Do not spray into eyes or onto the skin.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.

Keep container dry. Keep only in the original container.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store containers in upright position.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids.

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
111-76-2	2-Butoxyethanol	Europe: IOELV: STEL	246 mg/m ³ ; 50 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	98 mg/m ³ ; 20 ppm (may be absorbed through the skin)
		Great Britain: WEL-STEL	246 mg/m ³ ; 50 ppm (may be absorbed through the skin)
		Great Britain: WEL-TWA	123 mg/m ³ ; 25 ppm (may be absorbed through the skin)
		Ireland: 15 minutes	246 mg/m ³ ; 50 ppm (may be absorbed through the skin)
		Ireland: 8 hours	98 mg/m ³ ; 20 ppm (may be absorbed through the skin)
123-86-4	n-Butyl acetate	Europe: IOELV: STEL	723 mg/m ³ ; 150 ppm
		Europe: IOELV: TWA	241 mg/m ³ ; 50 ppm
		Great Britain: MEL/OES-STEL	966 mg/m ³ ; 200 ppm
		Great Britain: MEL/OES-TWA	724 mg/m ³ ; 150 ppm
		Ireland: 15 minutes	950 mg/m ³ ; 200 ppm
		Ireland: 8 hours	710 mg/m ³ ; 150 ppm
67-63-0	Isopropyl alcohol	Great Britain: WEL-STEL	1250 mg/m ³ ; 500 ppm
		Great Britain: WEL-TWA	999 mg/m ³ ; 400 ppm
		Ireland: 15 minutes	400 ppm (may be absorbed through the skin)
		Ireland: 8 hours	200 ppm (may be absorbed through the skin)
71-36-3	Butan-1-ol	Great Britain: WEL-STEL	154 mg/m ³ ; 50 ppm (may be absorbed through the skin)
		Ireland: 8 hours	20 ppm
64742-95-6	Hydrocarbons, C9, aromatics	Great Britain: WEL-TWA	500 mg/m ³ (Aromatics)
115-10-6	Dimethyl ether	Europe: IOELV: TWA	1920 mg/m ³ ; 1000 ppm
		Great Britain: WEL-STEL	958 mg/m ³ ; 500 ppm
		Great Britain: WEL-TWA	766 mg/m ³ ; 400 ppm
		Ireland: 8 hours	1920 mg/m ³ ; 1000 ppm

Biological limit values:

CAS No.	Designation	Type	Limit value	Parameter	Sampling
111-76-2	2-Butoxyethanol	Great Britain: BMGV, urine	240 mmol/mol creatinine	Butoxyacetic acid	end of exposure or end of shift

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area. Explosion protection required.

**Rostex 400ml Aerosoldose**

Material number A400

Page: 7 of 14

Personal protection equipment**Occupational exposure controls**

- Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Use combination filter type A-P2 according to EN 14387. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection: Protective gloves according to EN 374. Glove material: Nitrile rubber. Layer thickness: $\geq 0,4$ mm. Breakthrough time: >480 min. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed goggles according to EN 166.
- Body protection: Wear suitable protective clothing.
- General protection and hygiene measures: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Take off immediately all contaminated or soaked clothing. And wash it before reuse. Do not breathe vapour/aerosol. Avoid contact with skin and eyes. When using do not eat, drink or smoke. Wash hands before breaks and after work. Work place should be equipped with a shower and an eye rinsing apparatus. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance:	Form: Aerosol Colour: beige
Odour:	characteristic
Odour threshold:	No data available
pH:	3.5
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	-41 °C
Evaporation rate:	No data available
Flammability:	Extremely flammable aerosol.
Explosion limits:	LEL (Lower Explosion Limit): 1.10 Vol-% UEL (Upper Explosive Limit): 18.60 Vol-%
Vapour pressure:	at 20 °C: 5500 hPa
Vapour density:	No data available
Density:	at 20 °C: 0.77 g/cm ³
Water solubility:	partially soluble

**Rostex 400ml Aerosoldose**

Material number A400

Page: 8 of 14

Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	not self-igniting
Decomposition temperature:	No data available
Viscosity, kinematic:	No data available
Explosive properties:	Product is not explosive. Vapours can form explosive mixtures with air.
Oxidizing characteristics:	No data available

9.2 Other information

Ignition temperature:	230 °C
Solvent content:	20 %
Water content:	67.8 %

SECTION 10: Stability and reactivity**10.1 Reactivity**

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

	No decomposition when used properly.
Thermal decomposition:	No data available



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 2000 mg/kg.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 5000 mg/kg.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Skin Irrit. 2; H315 = Causes skin irritation.

Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Skin Sens. 1; H317 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Symptoms

Higher doses may have a narcotic effect.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

**Rostex 400ml Aerosoldose**

Material number A400

Page: 10 of 14

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**Waste key number: 16 05 04* = Dangerous materials containing gases in pressure containers/Aerosol
* = Evidence for disposal must be provided.Recommendation: Do not open with force or incinerate, even when empty.
Special waste. Dispose of waste according to applicable legislation.
Do not dispose of with household waste.**Package**Waste key number: 15 01 10* = packaging containing residues of or contaminated by dangerous substances.
* = Evidence for disposal must be provided.Recommendation: Empty carefully and completely, if possible.
Dispose of waste according to applicable legislation. Handle empty containers with care.
Incineration may cause explosion.**SECTION 14: Transport information****14.1 UN number**ADR/RID, IMDG, IATA-DGR:
UN 1950**14.2 UN proper shipping name**ADR/RID, IMDG: UN 1950, AEROSOLS
IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE**14.3 Transport hazard class(es)**ADR/RID: Class 2, Code: 5F
IMDG: Class 2, Subrisk -, see SP63
IATA-DGR: Class 2.1**14.4 Packing group**ADR/RID, IATA-DGR: not applicable
IMDG: -**14.5 Environmental hazards**

Marine pollutant: no

**Rostex 400ml Aerosoldose**

Material number A400

Page: 11 of 14

14.6 Special precautions for user**Land transport (ADR/RID)**

Warning board:	RID: Kemmler-number 23, UN number UN 1950
Hazard label:	2.1
Special provisions:	190 327 344 625
Limited quantities:	1 L
EQ:	E0
Package - Instructions:	P207 LP200
Package - Special provisions:	PP87 RR6 L2
Special provisions for packing together:	MP9
Tunnel restriction code:	D

Sea transport (IMDG)

EmS:	F-D, S-U
Special provisions:	63, 190, 277, 327, 344, 381, 959
Limited quantities:	See SP277
Excepted quantities:	E0
Package - Instructions:	P207, LP200
Package - Provisions:	PP87, L2
IBC - Instructions:	-
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	-
Tank instructions - Provisions:	-
Stowage and handling:	SW1 SW22
Segregation:	SG69
Properties and observations:	-
Segregation group:	none

Air transport (IATA)

Hazard label:	Flamm. gas
Excepted Quantity Code:	E0
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft:	Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only:	Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special provisions:	A145 A167 A802
Emergency Response Guide-Code (ERG):	10L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations - Great Britain**

Hazchem-Code:	-
	No data available

**Rostex 400ml Aerosoldose**

Material number A400

Page: 12 of 14

National regulations - EC member states

Volatile organic compounds (VOC):

67.75 % by weight

Labelling of packaging with <= 125mL content

Signal word:

Danger

Hazard statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P312 Call a POISON CENTER/doctor if you feel unwell.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to hazardous or special waste collection point.

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 40
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P3a.

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021
Version: 3.0
Language: en-GB,IE
Date of print: 15/7/2021

Rostex 400ml Aerosoldose

Material number A400

Page: 13 of 14

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

- H220 = Extremely flammable gas.
- H222 = Extremely flammable aerosol.
- H225 = Highly flammable liquid and vapour.
- H226 = Flammable liquid and vapour.
- H229 = Pressurised container: May burst if heated.
- H280 = Contains gas under pressure; may explode if heated.
- H302 = Harmful if swallowed.
- H304 = May be fatal if swallowed and enters airways.
- H312 = Harmful in contact with skin.
- H315 = Causes skin irritation.
- H317 = May cause an allergic skin reaction.
- H318 = Causes serious eye damage.
- H319 = Causes serious eye irritation.
- H332 = Harmful if inhaled.
- H335 = May cause respiratory irritation.
- H336 = May cause drowsiness or dizziness.
- H411 = Toxic to aquatic life with long lasting effects.
- H412 = Harmful to aquatic life with long lasting effects.
- EUH066 = Repeated exposure may cause skin dryness or cracking.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021
Version: 3.0
Language: en-GB,IE
Date of print: 15/7/2021

Rostex 400ml Aerosoldose

Material number A400

Page: 14 of 14

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL: Occupational Exposure Limit Value
AS/NZS: Australian Standards/New Zealand Standards
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EN: European Standard
EU: European Union
IATA: International Air Transport Association
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

Reason of change: Changes in section 1: product identifier (UFI)

Date of first version: 18/2/2019

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.