

**Soft-Clean 400ml Aerosoldose**

Material number 830712 K1

Page: 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name: Soft-Clean 400ml Aerosoldose

UFI: 1UH0-K097-X00X-GCQW

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: cleaner

1.3 Details of the supplier of the safety data sheet

Company name: EUROTECH Maier Ernst GmbH

Street/POB-No.: Herrschaftswiesen 5

Postal Code, city: AT-6842 Koblach

WWW: www.eurotech.at

E-mail: office@eurotech.at

Telephone: +43 (0)5523 53852

Telefax: +43 (0)5523 53852 4

Department responsible for information:

Telephone: +43 (0)5523 53852, Email: office@eurotech.at

1.4 Emergency telephone number

Giftzentrale Wien, Telephone: +43 (0)1-4064343

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to EC regulation 1272/2008 (CLP)**

Aerosol 1; H222; H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2; H315	Causes skin irritation.
STOT SE 3; H336	May cause drowsiness or dizziness.
Asp. Tox. 1; H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3; H412	Harmful to aquatic life with long lasting effects.
(EUH066)	Repeated exposure may cause skin dryness or cracking.

2.2 Label elements**Labelling (CLP)**

Signal word:

Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021
Version: 5.1
Language: en-GB,IE
Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 2 of 13

Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection.
P312	Call a POISON CENTER/doctor if you feel unwell.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains $\geq 30\%$ aliphatic hydrocarbons
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, $< 2\%$ aromatics
Naphtha (petroleum), hydrotreated light
and Pentane.

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.
Inhaling can lead to irritations of the respiratory tract and mucous membrane.
Higher doses may lead to a narcotic effect.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

 Revision date: 29/4/2021
 Version: 5.1
 Language: en-GB,IE
 Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 3 of 13

3.2 Mixtures

Hazardous ingredients:

Ingredient	Designation	Content	Classification
REACH 01-2119471843-32-xxxx list no. 927-241-2 CAS 1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	30 - 50 %	Flam. Liq. 3; H226. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 3; H412. (EUH066).
EC No. 265-151-9 CAS 64742-49-0	Naphtha (petroleum), hydrotreated light	10 - 20 %	Flam. Liq. 2; H225. Skin Irrit. 2; H315. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411.
REACH 01-2119459286-30-xxxx EC No. 203-692-4 CAS 109-66-0	Pentane	2.5 - 10 %	Flam. Liq. 1; H224. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411. (EUH066).
EC No. 203-448-7 CAS 106-97-8	Butane	20 - 30 %	Flam. Gas 1; H220. Compr. Gas; H280.
EC No. 200-827-9 CAS 74-98-6	Propane	< 10 %	Flam. Gas 1; H220. Press. Gas (Comp.); H280.
EC No. 200-857-2 CAS 75-28-5	Isobutane	< 10 %	Flam. Gas 1; H220. Press. Gas (Comp.); H280.

Full text of H- and EUH-statements: see section 16.

Additional information: Contains >=30% aliphatic hydrocarbons.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	IF exposed or concerned: Get medical advice/attention. First aider: Pay attention to self-protection!
In case of inhalation:	Move victim to fresh air; if necessary, provide artificial respiration or oxygen. Make sure he/she is warm and comfortable. Seek medical attention. If victim is at risk of losing consciousness, position and transport on their side.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently seek the immediate attention of an ophthalmologist.
After swallowing:	Do not induce vomiting. Immediately get medical attention. In case of vomiting, lay at least head on side.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, water spray jet or carbon dioxide.

In case of large fires: water spray jet or alcohol resistant foam.

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated.

On heating or in case of fire toxic gases may form.

In case of fire may be liberated: Carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Hazchem-Code: -

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow fire water to penetrate into surface or ground water. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe gas/vapour/aerosol. Avoid contact with the substance. Eliminate all ignition sources if safe to do so. Provide adequate ventilation. Take off immediately all contaminated clothing and wash it before reuse. Wear appropriate protective equipment. Keep unprotected people away. Cordon off downwind area at risk and warn inhabitants.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Thoroughly clean surrounding area. In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out). Never return spills in original containers for re-use.

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

6.4 Reference to other sections

Refer additionally to section 8 and 13.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021
Version: 5.1
Language: en-GB,IE
Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 5 of 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe gas/vapour/aerosol. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off immediately all contaminated clothing and wash it before reuse. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Work place should be equipped with a shower and an eye rinsing apparatus.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Vapours can form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store containers in upright position.

Hints on joint storage:

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Great Britain: WEL-TWA	1200 mg/m ³ (> or = C7, Normal and branched chain alkanes)
		Great Britain: WEL-TWA	800 mg/m ³ (> or = C7, Cycloalkanes)
64742-49-0	Naphtha (petroleum), hydrotreated light	Great Britain: WEL-TWA	1800 mg/m ³ (C5-C6 alkenes)
109-66-0	Pentane	Europe: IOELV: TWA	3000 mg/m ³ ; 1000 ppm
		Great Britain: WEL-TWA	1800 mg/m ³ ; 600 ppm
		Ireland: 8 hours	3000 mg/m ³ ; 1000 ppm
106-97-8	Butane	Great Britain: WEL-STEL	1810 mg/m ³ ; 750 ppm
		Great Britain: WEL-TWA	1450 mg/m ³ ; 600 ppm
		Ireland: 8 hours	1000 ppm
75-28-5	Isobutane	Ireland: 15 minutes	1000 ppm

**Soft-Clean 400ml Aerosoldose**

Material number 830712 K1

Page: 6 of 13

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment**Occupational exposure controls**

- Respiratory protection: Not necessary, if the room is well-ventilated. For short or minimal exposure: respiratory filter; in cases of longer exposure: supplied air respirator.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.
- Hand protection: Protective gloves according to EN 374
Glove material: Nitrile rubber - Layer thickness: $\geq 0,4$ mm.
Breakthrough time: ≤ 480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed goggles according to EN 166.
- Body protection: Flame retardant, antistatic and chemical resistant protective clothing.
- General protection and hygiene measures:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Use only non-sparking tools. Do not breathe gas/vapour/aerosol. Do not get in eyes, on skin, or on clothing. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Work place should be equipped with a shower and an eye rinsing apparatus.

Environmental exposure controls

Do not allow to enter into ground-water, surface water or drains.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Appearance: Form: Aerosol
Colour: colourless
- Odour: characteristic
- Odour threshold: not determined
- pH: not applicable
- Melting point/freezing point: not determined
- Initial boiling point and boiling range: not applicable
- Flash point/flash point range: -60 °C
- Evaporation rate: not applicable
- Flammability: Extremely flammable aerosol.
- Explosion limits: LEL (Lower Explosion Limit): 0.80 Vol-%
UEL (Upper Explosive Limit): 8.50 Vol-%
- Vapour pressure: at 20 °C: 2600 hPa
- Vapour density: not determined
- Density: at 20 °C: 0.64 g/mL
- Water solubility: insoluble

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021

Version: 5.1

Language: en-GB,IE

Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 7 of 13

Partition coefficient: n-octanol/water:	not determined
Auto-ignition temperature:	not self-igniting
Decomposition temperature:	No data available
Viscosity, dynamic:	not determined
Viscosity, kinematic:	not determined
Explosive properties:	Product is not explosive. Potentially explosive vapour/air mixtures may form.
Oxidizing characteristics:	No data available

9.2 Other information

Ignition temperature: 280 °C

SECTION 10: Stability and reactivity**10.1 Reactivity**

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects:	<p>The statements are derived from the properties of the single components. No toxicological data is available for the product as such.</p> <p>Acute toxicity (oral): Based on available data, the classification criteria are not met. ATEmix calculated: > 2000 mg/kg</p> <p>Acute toxicity (dermal): Based on available data, the classification criteria are not met. ATEmix calculated: > 2000 mg/kg</p> <p>Acute toxicity (inhalative): Based on available data, the classification criteria are not met. ATEmix calculated (Vapours): > 20 mg/L</p> <p>Skin corrosion/irritation: Skin Irrit. 2; H315 = Causes skin irritation.</p> <p>Serious eye damage/irritation: Based on available data, the classification criteria are not met.</p> <p>Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.</p> <p>Skin sensitisation: Based on available data, the classification criteria are not met.</p> <p>Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.</p> <p>Carcinogenicity: Based on available data, the classification criteria are not met.</p> <p>Reproductive toxicity: Based on available data, the classification criteria are not met.</p> <p>Effects on or via lactation: Lack of data.</p> <p>Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.</p> <p>Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.</p> <p>Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.</p>
Other information:	<p>Information about Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: LD50 Rat, oral: > 5000 mg/kg LD50 Rabbit, dermal: > 5000 mg/kg</p> <p>Information about Naphtha (petroleum), hydrotreated light: LD50 Rat, oral: > 5000 mg/kg. (OECD 401) LD50 Rabbit, dermal: > 2000 mg/kg (OECD 402) LC50 Rat, inhalative (vapour) > 5.61 mg/L /4h (OECD 403)</p> <p>Information about Pentane: LD50 Rat, oral: > 5000 mg/kg LC50 Rat, inhalative > 20 mg/L/4h</p>

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021

Version: 5.1

Language: en-GB,IE

Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 9 of 13

SECTION 12: Ecological information**12.1 Toxicity**

Aquatic toxicity: Harmful to aquatic life with long lasting effects.

Information about Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Fish toxicity:

LL50 Oncorhynchus mykiss: > 100 mg/L/48h

Daphnia toxicity:

NOELR Daphnia magna (Big water flea): 0.317 mg/L/21d

Algae toxicity:

EL50 Pseudokirchneriella subcapitata (green algae): > 1000 mg/L/24h

Bacterial toxicity:

EL50 Tetrahymena pyriformis: 1.065 mg/L/48h

Information about Pentane:

Fish toxicity:

LL50 Oncorhynchus mykiss: 27.55 mg/L/96h

Daphnia toxicity:

EL50 Daphnia magna (Big water flea): 48.11 mg/L/48h

Algae toxicity:

NOEC Pseudokirchneriella subcapitata (green algae): 4.55 mg/L/72h

Bacterial toxicity:

NOEL Tetrahymena pyriformis: 23.7 mg/L/48h

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
not determined

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste key number: 16 05 04* = Dangerous materials containing gases in pressure containers/Aerosol
* = Evidence for disposal must be provided.

Recommendation: Do not pierce or burn, even after use.
Special waste. Dispose of waste according to applicable legislation.
Do not dispose of with household waste.
Do not empty into drains.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021

Version: 5.1

Language: en-GB,IE

Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 10 of 13

Package

Waste key number: 15 01 10* = metallic packaging

* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation. Empty carefully and completely, if possible. Handle empty containers with care. Incineration may cause explosion.

SECTION 14: Transport information**14.1 UN number**

ADR/RID, IMDG, IATA-DGR:

UN 1950

14.2 UN proper shipping name

ADR/RID, IMDG: UN 1950, AEROSOLS

IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID: Class 2, Code: 5F

IMDG: Class 2.1, Subrisk -

IATA-DGR: Class 2.1

**14.4 Packing group**

ADR/RID, IATA-DGR: not applicable

IMDG: -

14.5 Environmental hazards

Marine pollutant: no

14.6 Special precautions for user**Land transport (ADR/RID)**

Warning board: RID: Kemmler-number 23, UN number UN 1950

Hazard label: 2.1

Special provisions: 190 327 344 625

Limited quantities: 1 L

EQ: E0

Package - Instructions: P207 LP200

Package - Special provisions: PP87 RR6 L2

Special provisions for packing together: MP9

Tunnel restriction code: D

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021

Version: 5.1

Language: en-GB,IE

Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 11 of 13

Sea transport (IMDG)

EmS: F-D, S-U
Special provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantities: 1000 mL
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations - Great Britain**

Hazchem-Code: -
No data available

National regulations - EC member states

Volatile organic compounds (VOC):
100 % by weight = 640 g/L

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021

Version: 5.1

Language: en-GB,IE

Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 12 of 13

Labelling of packaging with <= 125mL content

Signal word:

Danger

Hazard statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P312 Call a POISON CENTER/doctor if you feel unwell.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to hazardous or special waste collection point.

Further regulations, limitations and legal requirements:

No data available

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information**Further information**

Wording of the H-phrases under paragraph 2 and 3:

H220 = Extremely flammable gas.
H222 = Extremely flammable aerosol.
H224 = Extremely flammable liquid and vapour.
H225 = Highly flammable liquid and vapour.
H226 = Flammable liquid and vapour.
H229 = Pressurised container: May burst if heated.
H280 = Contains gas under pressure; may explode if heated.
H304 = May be fatal if swallowed and enters airways.
H315 = Causes skin irritation.
H336 = May cause drowsiness or dizziness.
H411 = Toxic to aquatic life with long lasting effects.
H412 = Harmful to aquatic life with long lasting effects.
EUH066 = Repeated exposure may cause skin dryness or cracking.

**SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830

Revision date: 29/4/2021

Version: 5.1

Language: en-GB,IE

Date of print: 15/7/2021

Soft-Clean 400ml Aerosoldose

Material number 830712 K1

Page: 13 of 13

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
AS/NZS: Australian Standards/New Zealand Standards
ATEmix: Acute Toxicity Estimate of mixture
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EL50: Effective loading rate 50%
EN: European Standard
EU: European Union
IATA: International Air Transport Association
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LC50: Median lethal concentration
LD50: Lethal dose 50%
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
STOT SE: Specific target organ toxicity - single exposure
UN: United Nations
vPvB: Very persistent and very bioaccumulative

Reason of change: Changes in section 1: product identifier (UFI)

Date of first version: 15/11/2017

Department issuing data sheet

Contact person: see section 1: Department responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.