



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Bike Finish

UFI: R910-Y0CD-H00C-RK87

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Care product

1.3 Details of the supplier of the safety data sheet

Company name: EUROTECH Maier Ernst GmbH

Street/POB-No.: Herrschaftswiesen 5

Postal Code, city: AT-6842 Koblach

WWW: www.eurotech.at

E-mail: office@eurotech.at

Telephone: +43 (0)5523 53852

Telefax: +43 (0)5523 53852 4

Department responsible for information:

Telephone: +43 (0)5523 53852, Email: office@eurotech.at

1.4 Emergency telephone number

GIZ-Nord, Göttingen

Telephone: +49 551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
(EUH066) Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Labelling (CLP)



Signal word:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P242

Use only non-sparking tools.

P251

Do not pierce or burn, even after use.

P261

Avoid breathing spray.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501

Dispose of contents/container to hazardous or special waste collection point.



2.3 Other hazards

Inhalation causes narcotic effects/intoxication.

Contact with the liquid may lead to eye and skin irritation.

Exposure to temperatures exceeding 50 °C will increase pressure: resulting in danger of bursting or explosion.

In use, may form flammable/explosive vapour-air mixture.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Blend of active ingredients with propellant

Hazardous ingredients:

Identifiers	Designation Classification	Content
EC No. 265-150-3 CAS 64742-48-9	Naphtha (petroleum), hydrotreated heavy, pure Asp. Tox. 1; H304. (EUH066).	20 - 30 %
EC No. 203-448-7 CAS 106-97-8	n-Butane, pure Flam. Gas 1; H220. Press. Gas (Liq.); H280.	10 - 20 %
EC No. 200-857-2 CAS 75-28-5	Isobutane, pure Flam. Gas 1; H220. Press. Gas (Comp.); H280.	1 - 10 %
EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1; H220. Press. Gas (Comp.); H280.	1 - 10 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	Seek medical assistance when anyone has symptoms apparently due to inhalation or contact with skin or eyes. First aider: Pay attention to self-protection!
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. If the casualty has difficulty breathing, call a doctor immediately. In case of irregular breathing or respiratory arrest provide artificial respiration. If victim is at risk of losing consciousness, position and transport on their side.
Following skin contact:	Change contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.
After swallowing:	Swallowing is not regarded as a possible way of exposition.

**4.2 Most important symptoms and effects, both acute and delayed**

In case of inhalation: Inhalation causes narcotic effects/intoxication.

The following symptoms may occur: Nausea, drowsiness, headache, agitation, fatigue, dizziness, unconsciousness. Danger of serious damage to health by prolonged exposure.

After contact with skin:

May cause irritations. Repeated exposure may cause skin dryness or cracking.

After eye contact: Irritation and redness may occur.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media: Extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable. With air, vapours form potentially explosive mixtures, which are heavier than air. Beware of reignition.

May form dangerous gases and vapours in case of fire.

In case of fire may be liberated: Carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained breathing apparatus. Suitable protective clothing.

Additional information:

Cool endangered containers with water spray and, if possible, remove from danger zone.

Heating causes rise in pressure with risk of bursting.

Use water spray jet to knock down vapours.

Do not allow fire water to penetrate into surface or ground water.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Eliminate all ignition sources if safe to do so.

Avoid contact with the substance.

Wear appropriate protective equipment. Keep unprotected people away.

Do not breathe vapour/aerosol. Provide adequate ventilation.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

6.3 Methods and material for containment and cleaning up

Take up with non-flammable, liquid binding material (e.g. sand/earth/diatomaceous earth/vermiculit) and perform disposal according to instructions. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

6.4 Reference to other sections

Refer additionally to section 8 and 13.



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.
Avoid contact with skin and eyes. Do not breathe vapour/aerosol.
Wear appropriate protective equipment.

Precautions against fire and explosion: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.
Use only non-sparking tools. Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers: Keep container tightly closed in a cool, well-ventilated place.
Protect from heat and direct sunlight.

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids.
Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
106-97-8	n-Butane, pure	Ireland: 8 hours	1000 ppm
75-28-5	Isobutane, pure	Ireland: 15 minutes	1000 ppm

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.
Use filter type A (= against vapours of organic substances) according to EN 14387.
The following applies to propane in general:
If the concentration is exceeded, closed-circuit breathing apparatus must be used!
Have a breathing apparatus that is not dependent on the circulating air ready for emergencies.

Hand protection: Protective gloves according to EN 374.
Glove material: Nitrile rubber.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Solvent-resistant protective clothing.

General protection and hygiene measures: Keep away from heat sources, sparks and open flames.
When using do not eat, drink or smoke.
Change contaminated clothing.
Wash hands before breaks and after work.

Environmental exposure controls

Refer to "6.2 Environmental precautions".



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	Form: Aerosol
Colour:	yellow
Odour:	almost odourless
Odour threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	Extremely flammable.
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): 1.40 Vol-% UEL (Upper Explosive Limit): 32.00 Vol-%
Flash point/flash point range:	-60 °C
Auto-ignition temperature:	510 °C
Decomposition temperature:	No data available
pH:	No data available
Viscosity, kinematic:	No data available
Water solubility:	insoluble
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	4100 hPa
Density:	0.75 g/mL
Vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Product is not explosive. Potentially explosive vapour/air mixtures may form.
Oxidizing characteristics:	No data available
Auto-ignition temperature:	No data available
Evaporation rate:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Container under pressure.
Heating will lead to pressure increase: Danger of bursting and explosion.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect from direct exposure to sunlight and temperatures exceeding 50 °C.

10.5 Incompatible materials

Oxidising agent

10.6 Hazardous decomposition products

	In case of fire may be liberated: Carbon monoxide and carbon dioxide.
Thermal decomposition:	No data available



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects:

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

11.2 Information on other hazards

Endocrine disrupting properties: No data available

Symptoms

In case of inhalation: Inhalation causes narcotic effects/intoxication.

The following symptoms may occur: Nausea, drowsiness, headache, agitation, fatigue, dizziness, unconsciousness. Danger of serious damage to health by prolonged exposure.

After contact with skin:

May cause irritations. Repeated exposure may cause skin dryness or cracking.

After eye contact: Irritation and redness may occur.

SECTION 12: Ecological information

12.1 Toxicity

Further details:

No data available

12.2 Persistence and degradability

Further details:

Biodegradation: Poorly biodegradable.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information:

Do not allow to enter into ground-water, surface water or drains.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances

* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.
Do not dispose of with household waste.
Do not open with force or incinerate, even when empty.

Package

Waste key number: 15 01 10* = packaging containing residues of or contaminated by dangerous substances.

* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.
Empty carefully and completely, if possible.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR: UN 1950

14.2 UN proper shipping name

ADR/RID, IMDG: UN 1950, AEROSOLS

IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID: Class 2, Code: 5F

IMDG: Class 2, Subrisk -, see SP63

IATA-DGR: Class 2.1



14.4 Packing group

ADR/RID, IMDG, IATA-DGR: not applicable

14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant: no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: RID: Kemmler-number 23, UN number UN 1950

Hazard label: 2.1

Special Provisions: 190 327 344 625

Limited quantities: 1 L

EQ: E0

Package - Instructions: P207 LP200

Package - Special Provisions: PP87 RR6 L2

Special provisions for packing together: MP9

Tunnel restriction code: D

**SAFETY DATA SHEET**

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

Bike Finish

Material number 840600

Revision date: 25/1/2023

Version: 11.0

Replaces version: 10.1

Language: en-IE

Date of print: 3/2/2023

Page: 8 of 9

Sea transport (IMDG)

EmS: F-D, S-U
Special Provisions: 63 190 277 327 344 381 959
Limited quantities: See SP277
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations - EC member states**

Volatile organic compounds (VOC):

50 % by weight = 374 g/L

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances
[Seveso-III-Directive]

Physical hazards: Code P3a, Quantity threshold 150 000 kg / 500 000 kg

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H220 = Extremely flammable gas.

H222 = Extremely flammable aerosol.

H229 = Pressurised container: May burst if heated.

H280 = Contains gas under pressure; may explode if heated.

H304 = May be fatal if swallowed and enters airways.

EUH066 = Repeated exposure may cause skin dryness or cracking.

Reason of change: Changes in section 1: product identifier (UFI)

General revision

Date of first version: 14/4/2010



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

Bike Finish

Material number 840600

Revision date: 25/1/2023
Version: 11.0
Replaces version: 10.1
Language: en-IE
Date of print: 3/2/2023

Page: 9 of 9

Department issuing data sheet: **see section 1: Department responsible for information**

Abbreviations and acronyms:

- ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- Aerosol: Aerosol
- AS/NZS: Australian Standards/New Zealand Standards
- Asp. Tox.: Aspiration toxicity
- CAS: Chemical Abstracts Service
- CFR: Code of Federal Regulations
- CLP: Classification, Labelling and Packaging
- DMEL: Derived minimal effect level
- DNEL: Derived no-effect level
- EC: European Community
- EN: European Standard
- EQ: Excepted quantities
- EU: European Union
- Flam. Gas: Flammable gases
- IATA: International Air Transport Association
- IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
- IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
- IMDG Code: International Maritime Dangerous Goods Code
- LEL: Lower Explosion Limit
- MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
- OEL: Occupational Exposure Limit Value
- OSHA: Occupational Safety and Health Administration
- PBT: Persistent, bioaccumulative and toxic
- PNEC: Predicted no-effect concentration
- Press. Gas: Gases under pressure
- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
- TLV: Threshold Limit Value
- TRGS: Technical Rules for Hazardous Substances
- UN: United Nations
- vPvB: Very persistent and very bioaccumulative
- WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.