according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878



Material number 813400

Revision date:25/1/2023Version:15.3Replaces version:15.2Language:en-IEDate of print:3/2/2023Page:1 of 10

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

EUROTECH

Trade name:

LIEI

ne: Dry-Flon

C8F0-D0KA-S003-N47Y

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use:

Lubricating agent Parting agent

#### 1.3 Details of the supplier of the safety data sheet

Company name:	EUROTECH Maier Ernst GmbH
Street/POB-No.:	Herrschaftswiesen 5
Postal Code, city:	AT-6842 Koblach
WWW:	www.eurotech.at
E-mail:	office@eurotech.at
Telephone:	+43 (0)5523 53852
Telefax:	+43 (0)5523 53852 4

Department responsible for information:

Telephone: +43 (0)5523 53852, Email: office@eurotech.at

### 1.4 Emergency telephone number

GIZ-Nord, Göttingen Telephone: +49 551-19240

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2; H315	Causes skin irritation.
Eve Irrit. 2; H319	Causes serious eve irritation.
STOT SE 3: H336	May cause drowsiness or dizziness.
,	Toxic to aquatic life with long lasting effects.
· · · ·	1 5 5
(EUH066)	Repeated exposure may cause skin dryness or cracking.

### 2.2 Label elements

Labelling (CLP)



Signal word:	Danger	
Hazard statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.
	EUH066	Repeated exposure may cause skin dryness or cracking.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

Revision date:25/1/2023Version:15.3Replaces version:15.2Language:en-IEDate of print:3/2/2023Page:2 of 10

Precautionary statements:	P102	Keep out of reach of children.	
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
	P211	Do not spray on an open flame or other ignition source.	
	P251	Do not pierce or burn, even after use.	
	P271	Use only outdoors or in a well-ventilated area.	
	P273	Avoid release to the environment.	
	P280	Wear protective gloves/protective clothing/eye protection.	
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
	P391	Collect spillage.	
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
	P501	Dispose of contents/container to hazardous or special waste collection point.	
Special labelling Text for labelling:	Contains Isop	propyl alcohol.	

#### 2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect. Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

# **SECTION 3: Composition/information on ingredients**

3.1 Substances: not applicable

#### 3.2 Mixtures

Chemical characterisation: Mixture of the substances listed below with non-hazardous additions:

Hazardous ingredients:

Identifiers	Designation Classification	Content
EC No. 265-151-9 CAS 64742-49-0	Naphtha (petroleum), hydrotreated light, butadiene-free Flam. Liq. 1; H224. Skin Irrit. 2; H315. Aquatic Chronic 2; H411. (EUH066).	25 - 50 %
EC No. 200-661-7 CAS 67-63-0	Isopropyl alcohol Flam. Liq. 2; H225. Eye Irrit. 2; H319. STOT SE 3; H336.	5 - 25 %
EC No. 203-917-6 CAS 111-87-5	Octan-1-ol Eye Irrit. 2; H319. Aquatic Chronic 3; H412.	< 1 %
EC No. 204-126-9 CAS 9002-84-0	Polytetrafluorethylene Skin Irrit. 2; H315. Eye Irrit. 2; H319. STOT SE 3; H335.	< 0.5 %
EC No. 203-448-7 CAS 106-97-8	n-Butane, pure Flam. Gas 1; H220.  Press. Gas (Liq.); H280.	5 - 25 %
EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1; H220. Press. Gas (Comp.); H280.	5 - 25 %

Full text of H- and EUH-statements: see section 16.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

## **Dry-Flon**

Material number 813400

 Revision date:
 25/1/2023

 Version:
 15.3

 Replaces version:
 15.2

 Language:
 en-IE

 Date of print:
 3/2/2023

 Page:
 3 of 10

**SECTION 4: First aid measures** 

### 4.1 Description of first aid measures

General information:	First aider: Pay attention to self-protection!	
In case of inhalation:	Move victim to fresh air, put at rest and loosen restrictive clothing. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical treatment in case of troubles.	
Following skin contact:	After contact with skin, wash immediately with soap and plenty of water. Change contaminated clothing. Seek medical treatment in case of troubles.	
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.	
After swallowing:	Swallowing is not regarded as a possible way of exposition.	
4.2 Most important symptoms and effects, both acute and delayed		

Irritating to eyes and skin. May cause drowsiness or dizziness. Inhaling can lead to irritations of the respiratory tract and mucous membrane.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media: Foam, water spray jet, carbon dioxide, extinguishing powder.

Extinguishing media which must not be used for safety reasons

Full water jet.

#### 5.2 Special hazards arising from the substance or mixture

Extremely flammable. Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited. May form dangerous gases and vapours in case of fire. In case of fire may be liberated: Hydrogen fluoride, fluorohydrocarbons, carbon monoxide and carbon dioxide.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information: Use fine water spray to cool endangered containers. Danger of bursting container. Use water spray jet to knock down vapours.

Do not allow fire water to penetrate into surface or ground water.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so.

Do not breathe vapour/aerosol. Avoid contact with skin and eyes.

Wear appropriate protective equipment. Keep unprotected people away.

#### 6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains. If necessary notify appropriate authorities.

Respiratory protection:

The following applies to propane in general:

If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Respiratory protection must be worn whenever the WEL levels have been exceeded.

Provide good ventilation and/or an exhaust system in the work area.

#### Personal protection equipment

#### **Occupational exposure controls**

67-63-0 Isopropyl alcohol Ireland: 15 minutes 400 ppm (may be absorbed through the skin) Ireland: 8 hours 200 ppm (may be absorbed through the skin) Ireland: 8 hours 106-97-8 n-Butane, pure 1000 ppm 8.2 Exposure controls

#### 8.1 Control parameters Occupational exposure limit values

CAS No. Designation

SECTION 8: Exposure controls/personal protection	

#### Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids. Keep away from food, drink and animal feedingstuffs.

# 7.3 Specific end use(s)

Requirements for storerooms and containers:

No information available.

Type

Limit value

# Do not breathe vapour/aerosol. Do not spray into eyes or onto the skin.

SECTION 7: Handling and storage

Wear appropriate protective equipment.

Refer additionally to section 8 and 13.

Precautions against fire and explosion:

**EUROTECH** 

6.4 Reference to other sections

7.1 Precautions for safe handling

Additional information:

Advices on safe handling:

ot expose to temperatures exceeding 50 C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material

Provide adequate ventilation, and local exhaust as needed. Use only in well-ventilated areas.

s of ignition - No smoking.

Take precautionary measures against static discharges.

# 7.2 Conditions for safe storage, including any incompatibilities

Pressurized container: pro	otect from sunlig	ght and do no
°C. Do not pierce or burn	even after use	Do not spray

Use only non-sparking tools. Keep away from sources

Revision date: 25/1/2023 Version: 15.3 Replaces version: 15.2 en-IF Language: Date of print: 3/2/2023 4 of 10 Page

# SAFETY DATA SHEET

This material and its container must be disposed of in a safe way.

Use explosion-proof equipment and non-sparking tools/utensils.

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when

Dry-Flon

6.3 Methods and material for containment and cleaning up

pumping out).

Material number 813400

agents) and place in closed containers for disposal.



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

 Revision date:
 25/1/2023

 Version:
 15.3

 Replaces version:
 15.2

 Language:
 en-IE

 Date of print:
 3/2/2023

 Page:
 5 of 10

Hand protection:	Tightly sealed goggles according to EN 166. according to EN 374. Glove material: Nitrile rubber Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to EN 166.
Body protection:	Wear suitable protective clothing.
General protection and	hygiene measures:
	Keep away from heat sources, sparks and open flames.
	Change contaminated clothing.
	Do not breathe vapour/aerosol.
	When using do not eat, drink or smoke.
	Wash hands before breaks and after work.
	Have eye wash bottle or eye rinse ready at work place.

#### **Environmental exposure controls**

Refer to "6.2 Environmental precautions".

Dry-Flon Material number 813400

# **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	Form: Aerosol
Colour:	white, milky
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	-44 °C
Flammability:	Extremely flammable.
Upper/lower flammability or explosive limits:	No data available
Flash point/flash point range:	-97 °C
Decomposition temperature:	No data available
pH:	No data available
Viscosity, kinematic:	No data available
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	No data available
Density:	No data available
Vapour density:	No data available
Particle characteristics:	Not applicable
9.2 Other information	
Explosive properties:	Product is not explosive. Potentially explosive vapour/air mixtures may form.
Oxidizing characteristics:	No data available
Auto-ignition temperature:	No data available
Evaporation rate:	No data available
Additional information:	No data available

# **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

printed by EUROTECH

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

# Dry-Flon

Material number 813400

Revision date: 25/1/2023 Version: 15.3 Replaces version: 15.2 Language: en-IF 3/2/2023 Date of print: Page: 6 of 10

#### **10.2 Chemical stability**

**EUROTECH** 

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Container under pressure. Heating will lead to pressure increase: Danger of bursting and explosion.

#### 10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames. Protect from direct exposure to sunlight and temperatures exceeding 50 °C.

#### 10.5 Incompatible materials

None known

#### 10.6 Hazardous decomposition products

In case of fire may be liberated: Hydrogen fluoride, fluorohydrocarbons, carbon monoxide and carbon dioxide. No data available Thermal decomposition:

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects:

Acute toxicity (oral): Lack of data. Acute toxicity (dermal): Lack of data. Acute toxicity (inhalative): Lack of data. Skin corrosion/irritation: Skin Irrit. 2; H315 = Causes skin irritation. Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation. Sensitisation to the respiratory tract: Lack of data. Skin sensitisation: Lack of data. Germ cell mutagenicity/Genotoxicity: Lack of data. Carcinogenicity: Lack of data. Reproductive toxicity: Lack of data. Effects on or via lactation: Lack of data. Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness. Specific target organ toxicity (repeated exposure): Lack of data. Aspiration hazard: Based on available data, the classification criteria are not met. 11.2 Information on other hazards Endocrine disrupting properties: No data available

#### Symptoms

In case of inhalation: High concentrations irritate the mucous membranes. After contact with skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

# SECTION 12: Ecological information

#### 12.1 Toxicity

Aquatic toxicity:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

# S Dry-Flon

Material number 813400

Revision date:	25/1/2023
Version:	15.3
Replaces version	ion: 15.2
Language:	en-IE
Date of print:	3/2/2023
Page:	7 of 10

# 12.2 Persistence and degradability

Further details:

#### 12.3 Bioaccumulative potential

EUROTECH

Partition coefficient: n-octanol/water: No data available

No data available

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Endocrine disrupting properties

No data available

#### 12.7 Other adverse effects

General information: Do not allow to penetrate into soil, waterbodies or drains.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

ardous
is substances.

# **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR: UN 1950

#### 14.2 UN proper shipping name

ADR/RID, IMDG:	UN 1950, AEROSOLS
IATA-DGR:	UN 1950, AEROSOLS, FLAMMABLE

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878



**Dry-Flon** Material number 813400

Revision date:	25/1/2023
Version:	15.3
Replaces versi	on: 15.2
Language:	en-IE
Date of print:	3/2/2023
Page:	8 of 10

#### 14.3 Transport hazard class(es)

ADR/RID:	Class 2, Code: 5F
IMDG:	Class 2, Subrisk -, see SP63
IATA-DGR:	Class 2.1

#### 14.4 Packing group

ADR/RID, IMDG, IATA-DGR: not applicable

#### 14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is environmentally hazardous according to the criteria of the UN model regulations. yes

Marine pollutant:

#### 14.6 Special precautions for user

#### Land transport (ADR/RID)

Warning board:	RID: Kemmler-number 23, UN number UN 1950
Hazard label:	2.1
Special Provisions:	190 327 344 625
Limited quantities:	1 L
EQ:	E0
Package - Instructions:	P207 LP200
Package - Special Provisions:	PP87 RR6 L2
Special provisions for packing together:	MP9
Tunnel restriction code:	D
Sea transport (IMDG)	
EmS	ED SIL

EmS:	F-D, S-U
Special Provisions:	63 190 277 327 344 381 959
Limited quantities:	See SP277
Excepted quantities:	E0
Package - Instructions:	P207, LP200
Package - Provisions:	PP87, L2
IBC - Instructions:	-
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	-
Tank instructions - Provisions:	-
Stowage and handling:	SW1 SW22
Segregation:	SG69
Properties and observations:	-
Segregation group:	none

#### Air transport (IATA)

Hazard label: Flamm. gas Excepted Quantity Code: E0 Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg Cargo Aircraft only: Special Provisions: A145 A167 A802 Emergency Response Guide-Code (ERG): 10L

#### 14.7 Maritime transport in bulk according to IMO instruments

No data available



according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878



Dry-Flon Material number 813400 Revision date:25/1/2023Version:15.3Replaces version:15.2Language:en-IEDate of print:3/2/2023Page:9 of 10

**SECTION 15: Regulatory information** 

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations - EC member states

Labelling of packaging with <= 125mL content

	J.	
Signal word:	Danger	
Hazard statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H336	May cause drowsiness or dizziness.
	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements:	P102	Keep out of reach of children.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
		sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P271	Use only outdoors or in a well-ventilated area.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container to hazardous or special waste collection point.
Further regulations, limitation	is and legal requirem	ents:
		12/18/EU on the control of major-accident hazards involving dangerous substances
	[Seveso-III-	Directive]
	Physical ha	zards: Code P3a, Quantity threshold 150 000 kg / 500 000 kg
	Environmer	tal hazards: Code E2, Quantity threshold 200 000 kg / 500 000 kg

### **15.2 Chemical Safety Assessment**

For this mixture a chemical safety assessment is not required.

# **SECTION 16: Other information**

Wording of the H-phrases und	der paragraph 2 and 3:
- I	H220 = Extremely flammable gas.
	H222 = Extremely flammable aerosol.
	H224 = Extremely flammable liquid and vapour.
	H225 = Highly flammable liquid and vapour.
	H229 = Pressurised container: May burst if heated.
	H280 = Contains gas under pressure; may explode if heated.
	H315 = Causes skin irritation.
	H319 = Causes serious eye irritation.
	H335 = May cause respiratory irritation.
	H336 = May cause drowsiness or dizziness.
	H411 = Toxic to aquatic life with long lasting effects.
	H412 = Harmful to aquatic life with long lasting effects.
	EUH066 = Repeated exposure may cause skin dryness or cracking.
Reason of change:	General revision
Date of first version:	5/4/2006

Department issuing data sheet: see section 1: Department responsible for information

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

 Revision date: 25/1/2023

 Version:
 15.3

 Replaces version:
 15.2

 Language:
 en-IE

 Date of print:
 3/2/2023

 Page:
 10 of 10

Abbreviations and acronyms: ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road Aerosol: Aerosol Aquatic Chronic: Hazardous to the aquatic environment - chronic AS/NZS: Australian Standards/New Zealand Standards CAS: Chemical Abstracts Service CFR: Code of Federal Regulations CLP: Classification, Labelling and Packaging DMEL: Derived minimal effect level DNEL: Derived no-effect level EC: European Community EN: European Standard EQ: Excepted quantities EU: European Union Eye Irrit .: Eye irritation Flam. Gas: Flammable gases Flam. Liq.: Flammable liquid IATA: International Air Transport Association IATA-DGR: International Air Transport Association – Dangerous Goods Regulations IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk IMDG Code: International Maritime Dangerous Goods Code MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OEL: Occupational Exposure Limit Value OSHA: Occupational Safety and Health Administration PBT: Persistent, bioaccumulative and toxic PNEC: Predicted no-effect concentration Press. Gas: Gases under pressure REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail Skin Irrit.: Skin irritation STOT SE: Specific target organ toxicity - single exposure TLV: Threshold Limit Value TRGS: Technical Rules for Hazardous Substances UN: United Nations vPvB: Very persistent and very bioaccumulative WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

