



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Slidex 400 ml Aerosoldose

This safety data sheet applies to all pressure vessels (aerosol cans) exceeding 50 ml capacity.

UFI: NKE0-C025-A004-CDKF

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Lubricant

1.3 Details of the supplier of the safety data sheet

Company name: EUROTECH Maier Ernst GmbH

Street/POB-No.: Herrschaftswiesen 5

Postal Code, city: AT-6842 Koblach

WWW: www.eurotech.at

E-mail: office@eurotech.at

Telephone: +43 (0)5523 53852

Telefax: +43 (0)5523 53852 4

Department responsible for information:

Telephone: +43 (0)5523 53852, Email: office@eurotech.at

1.4 Emergency telephone number

GIZ-Nord, Göttingen

Telephone: +49 551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2; H319 Causes serious eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling (CLP)



Signal word:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.



SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

Slidex 400 ml Aerosoldose

Material number 800400

Revision date: 25/1/2023
Version: 13.3
Replaces version: 13.2
Language: en-IE
Date of print: 3/2/2023

Page: 2 of 9

Precautionary statements:	P102	Keep out of reach of children.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P261	Avoid breathing spray.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/protective clothing/eye protection.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P405	Store locked up.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains Isopropyl alcohol.

2.3 Other hazards

If higher concentrations occur: Inhalation causes narcotic effects/intoxication.

Potentially explosive mixtures may form if adequate ventilation is not provided.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Blend of active ingredients with propellant

Hazardous ingredients:

Identifiers	Designation Classification	Content
EC No. 265-200-4 CAS 64742-96-7	Solvent naphtha (petroleum), heavy aliph. Asp. Tox. 1; H304.	25 - 50 %
EC No. 200-661-7 CAS 67-63-0	Isopropyl alcohol Flam. Liq. 2; H225. Eye Irrit. 2; H319. STOT SE 3; H336.	10 - 25 %
EC No. 203-917-6 CAS 111-87-5	Octan-1-ol Eye Irrit. 2; H319. Aquatic Chronic 3; H412.	< 5 %
EC No. 200-827-9 CAS 74-98-6	Propane Flam. Gas 1; H220. Press. Gas (Comp.); H280.	10 - 25 %
EC No. 203-448-7 CAS 106-97-8	n-Butane, pure Flam. Gas 1; H220. Press. Gas (Liq.); H280.	10 - 25 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: First aider: Pay attention to self-protection!



- In case of inhalation: Move victim to fresh air; if necessary, provide artificial respiration or oxygen. Seek medical treatment in case of troubles.
- Following skin contact: Remove residues with soap and water. Change contaminated clothing. In case of skin reactions, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.
- After swallowing: Swallowing is not regarded as a possible way of exposition.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media: In case of fire, use sand, carbon dioxide or extinguishing powder. Never use water.

Extinguishing media which must not be used for safety reasons:

Water

5.2 Special hazards arising from the substance or mixture

Extremely flammable. Potentially explosive mixtures may form if adequate ventilation is not provided.

May form dangerous gases and vapours in case of fire.

In case of fire may be liberated: Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Cool endangered containers with water spray and, if possible, remove from danger zone.

Heating will lead to pressure increase: Danger of bursting and explosion.

Use water spray jet to knock down vapours.

Do not allow fire water to penetrate into surface or ground water.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.

Use only non-sparking tools. Wear appropriate protective equipment. Keep unprotected people away.

Avoid contact with skin and eyes. Provide adequate ventilation.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance. Do not remove residual product with water and detergent.

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

6.4 Reference to other sections

Refer additionally to section 8 and 13.



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide good ventilation and/or an exhaust system in the work area.
Do not spray in the eyes. Do not breathe vapour/aerosol.
Avoid contact with skin. Wear appropriate protective equipment.

Precautions against fire and explosion: Protect from direct exposure to sunlight and temperatures exceeding 50 °C. Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers: Keep container tightly closed in a cool, well-ventilated place.
Protect from heat and direct sunlight.

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids.
Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
67-63-0	Isopropyl alcohol	Ireland: 15 minutes	400 ppm (may be absorbed through the skin)
		Ireland: 8 hours	200 ppm (may be absorbed through the skin)
106-97-8	n-Butane, pure	Ireland: 8 hours	1000 ppm

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.
Use filter type A (= against vapours of organic substances) according to EN 14387.

The following applies to propane in general:
If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Hand protection: Protective gloves according to EN 374.
Glove material: nitrile rubber
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Wear suitable protective clothing.

General protection and hygiene measures:
Keep away from heat sources, sparks and open flames.
Do not breathe vapour/aerosol.
Avoid contact with skin and eyes.
Take off immediately all contaminated clothing.
Wash hands before breaks and after work.
Work place should be equipped with a shower and an eye rinsing apparatus.

Environmental exposure controls

Refer to "6.2 Environmental precautions".



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	Form: Aerosol
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flammability:	Extremely flammable.
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): (butane) 1.50 Vol-% UEL (Upper Explosive Limit): (Isopropyl alcohol) 12.00 Vol-%
Flash point/flash point range:	-60 - -42 °C
Decomposition temperature:	No data available
pH:	No data available
Viscosity, kinematic:	No data available
Water solubility:	slightly miscible
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	at 20 °C: (Propane) 7700 hPa
Density:	No data available
Vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Product is not explosive. Potentially explosive vapour/air mixtures may form.
Oxidizing characteristics:	No data available
Auto-ignition temperature:	No data available
Evaporation rate:	No data available
Additional information:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Container under pressure. Heating will lead to pressure increase: Danger of bursting and explosion.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect from direct exposure to sunlight and temperatures exceeding 50 °C.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

	In case of fire may be liberated: Carbon monoxide and carbon dioxide
Thermal decomposition:	No data available



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects:

- Acute toxicity (oral): Lack of data.
- Acute toxicity (dermal): Lack of data.
- Acute toxicity (inhalative): Lack of data.
- Skin corrosion/irritation: Lack of data.
- Serious eye damage/irritation: Eye Irrit. 2; H319 = Causes serious eye irritation.
- Sensitisation to the respiratory tract: Lack of data.
- Skin sensitisation: Lack of data.
- Germ cell mutagenicity/Genotoxicity: Lack of data.
- Carcinogenicity: Lack of data.
- Reproductive toxicity: Lack of data.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.
- Specific target organ toxicity (repeated exposure): Lack of data.
- Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties: No data available

Symptoms

In case of inhalation: High concentrations of vapours irritate the eyes and mucous membranes.
After resorption: Headache, dizziness, inebriation, unconsciousness.
After contact with skin:
Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

SECTION 12: Ecological information

12.1 Toxicity

Further details: No data available

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

Waste key number: 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances

* = Evidence for disposal must be provided.

Recommendation: This material and its container must be disposed of as hazardous waste.
Do not dispose of with household waste.
Do not open with force or incinerate, even when empty.

Package

Waste key number: 15 01 10* = Packaging containing residues of or contaminated by dangerous substances.
* = Evidence for disposal must be provided.

Recommendation: Empty carefully and completely, if possible.
Dispose of waste according to applicable legislation.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID, IMDG, IATA-DGR: UN 1950

14.2 UN proper shipping name

ADR/RID, IMDG: UN 1950, AEROSOLS

IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID: Class 2, Code: 5F

IMDG: Class 2, Subrisk -, see SP63

IATA-DGR: Class 2.1

**14.4 Packing group**

ADR/RID, IMDG, IATA-DGR: not applicable

14.5 Environmental hazards

Dangerous for the environment: Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant: no

14.6 Special precautions for user**Land transport (ADR/RID)**

Warning board: RID: Kemmler-number 23, UN number UN 1950

Hazard label: 2.1

Special Provisions: 190 327 344 625

Limited quantities: 1 L

EQ: E0

Package - Instructions: P207 LP200

Package - Special Provisions: PP87 RR6 L2

Special provisions for packing together: MP9

Tunnel restriction code: D

**SAFETY DATA SHEET**

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

Slidex 400 ml Aerosoldose

Material number 800400

Revision date: 25/1/2023

Version: 13.3

Replaces version: 13.2

Language: en-IE

Date of print: 3/2/2023

Page: 8 of 9

Sea transport (IMDG)

EmS: F-D, S-U
Special Provisions: 63 190 277 327 344 381 959
Limited quantities: See SP277
Excepted quantities: E0
Package - Instructions: P207, LP200
Package - Provisions: PP87, L2
IBC - Instructions: -
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: -
Tank instructions - Provisions: -
Stowage and handling: SW1 SW22
Segregation: SG69
Properties and observations: -
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. gas
Excepted Quantity Code: E0
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft: Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only: Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions: A145 A167 A802
Emergency Response Guide-Code (ERG): 10L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations - EC member states**

Volatile organic compounds (VOC):

approx. 100 % by weight

Labelling of packaging with <= 125mL content

Signal word:

Danger

Hazard statements:

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H336

May cause drowsiness or dizziness.

Precautionary statements:

P102

Keep out of reach of children.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

P261

Avoid breathing spray.

P271

Use only outdoors or in a well-ventilated area.

P312

Call a POISON CENTER/doctor if you feel unwell.

P405

Store locked up.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501

Dispose of contents/container to hazardous or special waste collection point.

**SAFETY DATA SHEET**

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) No 2020/878

Slidex 400 ml Aerosoldose

Material number 800400

Revision date: 25/1/2023

Version: 13.3

Replaces version: 13.2

Language: en-IE

Date of print: 3/2/2023

Page: 9 of 9

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances
[Seveso-III-Directive]

Physical hazards: Code P3a, Quantity threshold 150 000 kg / 500 000 kg

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H220 = Extremely flammable gas.

H222 = Extremely flammable aerosol.

H225 = Highly flammable liquid and vapour.

H229 = Pressurised container: May burst if heated.

H280 = Contains gas under pressure; may explode if heated.

H304 = May be fatal if swallowed and enters airways.

H319 = Causes serious eye irritation.

H336 = May cause drowsiness or dizziness.

H412 = Harmful to aquatic life with long lasting effects.

Reason of change: General revision

Date of first version: 26/1/2007

Department issuing data sheet: see section 1: Department responsible for information

Abbreviations and acronyms: ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aerosol: Aerosol
Aquatic Chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
Asp. Tox.: Aspiration toxicity
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EN: European Standard
EQ: Excepted quantities
EU: European Union
Eye Irrit.: Eye irritation
Flam. Gas: Flammable gases
Flam. Liq.: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
Press. Gas: Gases under pressure
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.